





SERIE B521-R

BEWEGLICH - ORIENTABILE

E-DRIVER INKLUSIV - E-DRIVER INCLUSO



44 MM AUSSCHNITT - FORO 44 MM



EIGENSCHAFTEN | CARATTERISTICHE

| Farbe<br>Colore                                                                     | Art. Nr.        | W     | CREE<br>COB  | LM     | K          | CRI<br>RA | Optik | Driver<br>inclusive |  |
|-------------------------------------------------------------------------------------|-----------------|-------|--------------|--------|------------|-----------|-------|---------------------|---------------------------------------------------------------------------------------|
|  | B521-R 27 3003E | 2,1 W | 700 mA - 3 V | 114 lm | 2700 K     | < 90      | 30°   | E                   | 44 mm                                                                                 |
|  | B521-R 27 3005E | 2,1 W | 700 mA - 3 V | 114 lm | 2700 K     | < 90      | 30°   | E                   | 44 mm                                                                                 |
|  | B521-R 30 3003E | 2,1 W | 700 mA - 3 V | 114 lm | 3000 K     | < 90      | 30°   | E                   | 44 mm                                                                                 |
|  | B521-R 30 3005E | 2,1 W | 700 mA - 3 V | 114 lm | 3000 K     | < 90      | 30°   | E                   | 44 mm                                                                                 |
|  | B521-R BL 3003E | 2,1 W | 700 mA - 3 V | 114 lm | blau - blu | < 90      | 30°   | E                   | 44 mm                                                                                 |
|  | B521-R BL 3005E | 2,1 W | 700 mA - 3 V | 114 lm | blau - blu | < 90      | 30°   | E                   | 44 mm                                                                                 |

LICHTVERTEILUNG | DISTRIBUZIONE DELLA LUCE

