




SERIE	B500 B566
POWER	6,8 W
LUMEN	657 lm
CREE COB	700 mA - 9 V
CRI / RA	> 90



Lebensdauer | vita: L80 B10 50.000h



Der LED Einsatz eignet sich für alle Ringe und Rahmen der Serie B5 ...
Il modulo LED è adatto a tutti gli anelli e cornici della serie B5 ...

IES - LDT


Download Homepage

Montageanleitung | Istruzioni montaggio


Download Homepage



MIT TRIAC DIM NETZTEIL | CON ALIMENTATORE TRIAC DIM




Art. Nr.	W	Lm	K	Driver
B566-27 38 70 ED	6,8 W	657	2700 K	ED
B566-30 38 70 ED	6,8 W	657	3000 K	ED
B566-40 38 70 ED	6,8 W	657	4000 K	ED




Art. Nr.	W	Lm	K	Driver
B566-27 60 70 ED	6,8 W	657	2700 K	ED
B566-30 60 70 ED	6,8 W	657	3000 K	ED
B566-40 60 70 ED	6,8 W	657	4000 K	ED

OHNE NETZTEIL | SENZA ALIMENTATORE






Art. Nr.	W	Lm	K	Driver
B566-27 38 70	6,8 W	657	2700 K	/
B566-30 38 70	6,8 W	657	3000 K	/
B566-40 38 70	6,8 W	657	4000 K	/



Art. Nr.	W	Lm	K	Driver
B566-27 60 70	6,8 W	657	2700 K	/
B566-30 60 70	6,8 W	657	3000 K	/
B566-40 60 70	6,8 W	657	4000 K	/

LICHTVERTEILUNG | DISTRIBUZIONE DELLA LUCE



DIMMER

Schalk	Universal Tastdimmer Regolatore a tasti universale	ETD U2 ETD 2E
Eltako	Universal-Dimmschalter Dimmer universale elettronico	EUD61NPN-UC EUD12NPN-UC

OPTIONAL | OPZIONALE



☐ **B566-RR15**
Reflektor | Riflettore 15°



☐ **B566-RR25**
Reflektor | Riflettore 25°



☒ **B566-RR6004**
Reflektor gold | Riflettore oro 60°