

SPOT MINI AUSSEN | SPOT MINI PER ESTERNO

■
■
■
■
 LED LIGHTING





SERIE B79-OS

OUTDOOR

SPOT MINI AUSSEN
SPOT MINI PER ESTERNO


BEWEGLICH - ORIENTABILE




EIGENSCHAFTEN | CARATTERISTICHE

Art. Nr.	W	Volt	CREE COB	LM	K	CRI	Optik	Material	Anschlusskabel Cavo di connessione
B79-OS 2750	4,2 W	230 V	✓	502 lm	2700 K	< 90	50°	IK 06	1,5 m H05RN-F 3 x 0,75mm ²
B79-OS 3050	4,2 W	230 V	✓	502 lm	3000 K	< 90	50°	IK 06	1,5 m H05RN-F 3 x 0,75mm ²
B79-OS 4050*	4,2 W	230 V	✓	502 lm	4000 K	< 90	50°	IK 06	1,5 m H05RN-F 3 x 0,75mm ²

LICHTVERTEILUNG | DISTRIBUZIONE DELLA LUCE



ZUBEHÖR | ACCESSORI



B79-OSB0105
Blendaufsatz
Schermo antiabbagliamento



B79-OS2E05
Erdspieß
Picchetto

*keine Lagerware, nur auf Bestellung | *non gestito a magazzino, solo su ordinazione

03.2023 | Änderungen vorbehalten, Angaben ohne Gewähr | Con riserva di modifiche. Informazioni senza garanzia

www.brilux.it | info@brilux.it