

SPOT MEDIUM AUSSEN

| SPOT MEDIUM PER ESTERNO

LED LIGHTING





SERIE B82-OS

OUTDOOR

SPOT MEDIUM AUSSEN

SPOT MEDIUM PER ESTERNO


BEWEGLICH - ORIENTABILE




EIGENSCHAFTEN | CARATTERISTICHE

Art. Nr.	W	Volt	CREE COB	LM	K	CRI	Optik	Material	Anschlusskabel Cavo di connessione
B82-OS 2750	8,4 W	230 V	✓	754 lm	2700 K	< 90	50°	IK 06	1,5 m H05RN-F 3 x 0,75mm²
B82-OS 3050	8,4 W	230 V	✓	754 lm	3000 K	< 90	50°	IK 06	1,5 m H05RN-F 3 x 0,75mm²
B82-OS 4050*	8,4 W	230 V	✓	754 lm	4000 K	< 90	50°	IK 10	1,5 m H05RN-F 3 x 0,75mm²
B82-OS 30 0350	8,4 W	700 mA	✓	850 lm	3000 K	< 90	3°	IK 06	1,5 m H05RN-F 3 x 0,75mm²

LICHTVERTEILUNG | DISTRIBUZIONE DELLA LUCE



ZUBEHÖR | ACCESSORI



B82-OSB1105

Blendaufsatz

Schermo antiabbagliamento



B82-OS2E05

Erdspieß

Picchetto