

DLD DALI/DMX 4CH LED DIM DRIVER CC/CV ■ ■ ■ ■ LED LIGHTING



SERIE DLD DALI | B96-DLD

**Ausgang: CC (Konstant-Strom) /
CV (Konstant-Spannung)**

**Uscita: CC (corrente costante) /
CV (tensione costante)**

PUSH | 1 / 0 - 10 V PWM DALI | DMX

Für DIN-Schiene | Per DIN RAIL



EIGENSCHAFTEN | CARATTERISTICHE

Art. Nr.	W	V in	Amp.	V out	Amp. out	IP	ta	Dimensions	VP
CC (Konstant-Strom corrente costante)									
B96-DLD1248-4CCD	12 - 134 W	12 - 48 VDc	/	12 - 48 VDc	4 x 250 - 700 mA (1 x 2800)	20	-40 ... +60°C	72 x 92 x 62 mm	/
CV (Konstant-Spannung tensione costante)									
B96-DLD1248-4CVD	240 - 960 W	12 - 48 VDc	/	12 - 48 VDc	4 x 5 A (1 x 20)	20	-40 ... +60°C	72 x 92 x 62 mm	/
B96-DLD1248-4CVX	240 - 960 W	12 - 48 VDc	/	12 - 48 VDc	4 x 5 A (1 x 20)	20	-40 ... +60°C	72 x 92 x 62 mm	/

