

PE TRIAC DIM DRIVER LED CC




SERIE PE TRIAC DIM | B96-PE

Ausgang: CC (Konstant-Strom)

Uscita: CC (corrente costante)

LED Netzteil On / Off | TRIAC DIM

LED Alimentatore On / Off | TRIAC DIM



EIGENSCHAFTEN | CARATTERISTICHE

Art. Nr.	W	V in	Amp.	V out	Amp. out	IP	ta	Dimensions	VP
B96-PE294R4225	10 W	200 - 240 VAc	/	25 - 42 VDC	250 mA	IP 20	-20 ... +60°C	115 x 40 x 26 mm	/
B96-PE294B4233	12,80 W	200 - 240 VAc	/	25 - 37 VDC	330 mA	IP 20	-20 ... +60°C	115 x 40 x 26 mm	/
B96-PE294B1270	10,5 W	200 - 240 VAc	/	6 - 15 VDC	700 mA	IP 20	-20 ... +60°C	115 x 40 x 26 mm	/

DIMMER MODELLE

Berker	2867 10, 2866 10, 2874 10
Eltako	EUD12NPN-UC, EUD61NPN-UC
Vimar	Plana14153 +3%
Relco	RM857, RTS34DSL +3%

MONTAGEANLEITUNG | ISTRUZIONI MONTAGGIO

