






SERIE	BD5
POWER	5,3 W
LUMEN	578 lm
CREE COB	250 mA - 21 V
CRI / RA	> 90



Lebensdauer | vita: L80 B10 50.000h

OHNE NETZTEIL | SENZA ALIMENTATORE



Art. Nr.	W	Lm	K	Driver
BD5-275025	5,3 W	578	2700 K	/
BD5-305025	5,3 W	578	3000 K	/
BD5-405025	5,3W	578	4000 K	/


TRIAC DIM NETZTEIL | ALIMENTATORE TRIAC DIM

Art. Nr.	W	V in	Amp.	V out	Amp. out	IP	ta	Dimensions	VP
B96-PE294R4225	10 W	200 - 240 VAc	/	25 - 42 VDC	250 mA	IP 20	-20 ... +60°C	115 x 40 x 26 mm	/

andere Dali/KNX Driver | altri Dali/KNX driver:


> Siehe www.brilux.it/driver-dimmer | visita www.brilux.it/driver-dimmer

LICHTVERTEILUNG | DISTRIBUZIONE DELLA LUCE



DIMMER

Schalk	Universal Tastdimmer Regolatore a tasti universale	ETD U2 ETD 2E
Eltako	Universal-Dimmschalter Dimmer universale elettronico	EUD61NPN-UC EUD12NPN-UC



ZUBEHÖR INNENRINGE | ACCESSORI ANELLI INTERNI



BD5-RIC52..
Ring konisch
Anello conico



BD5-RIF52..
Ring flat
Anello flat



BD5-RIR52..
Ring abgerundet
Anello curvato